

Bricktrend

DECO

The Bricktrend Collection features a three-tone base made up of soft shades of textured stone, enhanced by the small 8x33cm format, which creates a thinner, trendier line, as the name suggests.

The collection is completed with the addition of decorative bricks which match each of the base tones. Adorned with raised, classic motifs, engraved onto the stone itself and subtly worn down, for a romantic, timeless air.

Bricktrend is a reinterpretation of the brick as a design object, giving real added value to a space.



Deco Bricktrend Almond 8,15x33,15 / 3,2"x 13,1"



Deco Bricktrend Almond 8,15x33,15 / 3,2"x 13,1"




Deco Bricktrend Almond 8,15x33,15 / 3,2"x 13,1" - Bricktrend Almond 8,15x33,15 / 3,2"x 13,1"



Deco Bricktrend White 8,15x33,15 / 3,2"x 13,1" - Bricktrend White 8,15x33,15 / 3,2"x 13,1" - Bricktrend Grey 8,15x33,15 / 3,2"x 13,1"



Bricktrend White
8,15x33,15 / 3,2”x 13,1”




Deco Bricktrend White
8,15x33,15 / 3,2”x 13,1”



Bricktrend Almond
8,15x33,15 / 3,2”x 13,1”



Deco Bricktrend Almond
8,15x33,15 / 3,2”x 13,1”



Bricktrend Grey
8,15x33,15 / 3,2”x 13,1”



Deco Bricktrend Grey
8,15x33,15 / 3,2”x 13,1”

Bricktrend

DECO



FROST-PROOF



MATTE



SLIGHT
VARIATION

TECHNICAL DATA

COLOUR	BENDING ISO-10545-4	HARDNESS MOHS/EN-101	ABRASION-PEI ISO-10545-7	CRAZING ISO-10545-11	CHEMICAL ATTACK RESISTANCE (ISO-10545-13)				FROST R. ISO-10545-12	SLIP RESISTANCE DIN 51130-R	SLIP RESISTANCE UNE-ENV 12633	GROUP
					STAINS	CLEANING AGENTS	POOL ADDITIVES	ACIDS/BASES				
BRICKTREND WHITE	≥ 35	6	IV	PASS	5	GA	GA	GLA/GHA	PASS	R-9	1	C
DECO BRICKTREND WHITE	≥ 35	6	-	PASS	5	GA	GA	GLA/GHA	PASS	-	-	W
BRICKTREND ALMOND	≥ 35	6	IV	PASS	5	GA	GA	GLA/GHA	PASS	R-9	1	C
DECO BRICKTREND ALMOND	≥ 35	6	-	PASS	5	GA	GA	GLA/GHA	PASS	-	-	W
BRICKTREND GREY	≥ 35	6	IV	PASS	5	GA	GA	GLA/GHA	PASS	R-9	1	C
DECO BRICKTREND GREY	≥ 35	6	-	PASS	5	GA	GA	GLA/GHA	PASS	-	-	W

All formats of our paving and tiling meet European standard EN-UNE-14411 and our parameters of length, width, thickness, orthogonality and planarity meet standard UNE - EN ISO 10545-2. Avoid applying white or red tile adhesive outdoors WHERE THERE IS A RISK OF FROST. Suitable for use in outdoor areas where this is a risk of frost.

PACKING LIST

SIZE	ITEM	PCS / BOX	SQM / BOX	BOX / PAL	SQM / PAL	KG / BOX	KG / SQM	KG / PAL
8,15x33,15	BRICKTREND / DECO BRICKTREND	46	1,24	54	66,96	20,71	16,7	1118